



LEGEND

- A. NEOPRENE CORE $\phi 0.75$
- B. DOUBLE SHIELD, #34 AWG TC, 80% COVERAGE
- C. SEMICONDUCTIVE EPR, 0.020 WALL
- D. INSULATING EPR 0.193 WALL
- E. SHIELD, #28 AWG TC, 85% COVERAGE.
- F. MYLAR TAPE, 0.05 WALL
- G. SHIELD, #28 AWG, TC, 80% COVERAGE
- H. JACKET, PVC, BLACK

REVISIONS

THIS DOCUMENT AND THE INFORMATION CONTAINED IN IT ARE THE PROPERTY OF DIELECTRIC SCIENCES, INC AND SHALL NOT BE REPRODUCED OR COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OF APPARATUS WITHOUT PERMISSION.

REV	ECO NUMBER	APPD	DATE
-	RELEASE DRAWING		

UNLESS OTHERWISE SPECIFIED	
DIMENSIONS ARE IN INCHES TOLERANCE ON	
DECIMALS .XX ±.01 .XXX ±.005	ANGLES ±
CONCENTRICITY .005 TIR REMOVE BURRS & SHARP EDGES ALL MACHINE SURFACES 125 \checkmark	

DRAWN JEH	DATE 20FEM85
CHECKED	DATE
APPROVED	DATE
MATERIAL	
FINISH	

DIELECTRIC SCIENCES, INC			
CHELMSFORD, MASSACHUSETTS 01824			
PULSE CABLE, TRIAXIAL 14 OHM, 22.5 KVDC			
SIZE A	FSCM NO. 50509	DWG NO. 2122	REV
SCALE		SHEET	1 OF 1