


A-882 SPST, 1600 Amps, 28 VDC


Features:

- SPST Main Contacts
- Economizing Coil
- 28 VDC
- 1600 Amps
- High Reliability
- Meets many requirements of MIL-R-6106



Dimensions for this product are expressed in inches.
Multiply values by 25.4 for millimeters.

CONTACTOR CONFIGURATION



Notes:

For factory-direct application assistance, contact the HARTMAN product team at (419) 521-9500, Fax (419) 526-2749.

© 2004 by Tyco Electronics Corporation. All Rights Reserved.
HARTMAN and TYCO are trademarks.

PRODUCT SPECIFICATIONS

| | |
|-------------------------------|--------------------------|
| Construction | Gasket Sealed |
| Main Contacts: | |
| Configuration | SPST N.O. |
| Voltage (Nominal) | 28 VDC |
| Current (Resistive) | 1600 Amps |
| Coil Data: | |
| Duty Cycle | Continuous (Economizing) |
| Voltage (Nominal) | 28 VDC |
| Pick-Up Voltage | 18 VDC Maximum |
| Drop-Out Voltage | 1 - 7 VDC |
| Coil Current @ 28 VDC & +25°C | |
| In-Rush | 1.87 Amps |
| Hold | 1.12 Amps |
| Operating Temperature | -55°C to +71°C |
| Life: | |
| Electrical | 50,000 Cycles |
| Mechanical | 100,000 Cycles |
| Weight Maximum | 10 Lbs. 12 Oz. |