



BR-329BC 2PST N.O., 60 Amps, 115 VAC, 60 Hz




Features:

- 2PST N.O. Main Contacts
- 115 VAC Coil
- 115 VAC, 60 Hz
- 60 Amps
- High Reliability
- Meets many requirements of MIL-R-6106
- Light Weight Construction



Dimensions for this product are expressed in inches.
Multiply values by 25.4 for millimeters.

CONTACTOR CONFIGURATION



Notes:

PRODUCT SPECIFICATIONS

Construction	Gasket Sealed, Vented
Main Contacts:	
Configuration	2PST N.O.
Voltage (Nominal)	115 VAC, 60 Hz
Current (Resistive)	60 Amps
Coil Data:	
Duty Cycle	Continuous
Voltage (Nominal)	115 VAC, 60 Hz
Pick-Up Voltage	90 VAC
Drop-Out Voltage	5 - 45 VAC
Coil Current @ 115 VAC & +25°C	0.107 Amps Maximum
Operating Temperature	-55°C to +71°C
Life:	
Electrical	50,000 Cycles
Mechanical	100,000 Cycles
Weight	1 Lb.

For factory-direct application assistance, contact the HARTMAN product team at (419) 521-9500, Fax (419) 526-2749.

© 2004 by Tyco Electronics Corporation. All Rights Reserved.
HARTMAN and TYCO are trademarks.

Catalog (web doc only)
Revised 5-04

www.tycoelectronics.com

Dimensions are in inches and millimeters unless otherwise specified. Values in brackets are metric equivalents.

Dimensions are shown for reference purposes only. Specifications subject to change.

USA: 1-800-522-6752
Canada: 1-905-470-4425
Mexico: 01-800-733-8926
C. America: 52-55-5-729-0425

South America: 55-11-3611-1514
Hong Kong: 852-2735-1628
Japan: 81-44-844-8013
UK: 44-141-810-8967