

SPECIFICATION FOR APPROVAL

CERAMIC DISC CAPACITORS								
Customer :								
Capacitance : 3,300 pF		Tolerance: ±10 %		Issue No.				
Temp. Coef. Y5P		Q'ty of Sample: pcs		Issue Day. 27/10/2020				
Cust. P/N:		Part No. KB3I332K-L018BD23		W V 6,300 VDC				
Diagram of Dimensions : (Unit : mm)								
			D: 23.0 max. T: 7.5 max. F: 10.0 ±1.0 L: 25.0 min. d: 0.8 ±0.1 P: 4.0 max.					
SPECIFICATION				Initial Test				
				No.	pF	Tanδ	I.R.	T.V.
Frequency = 1K Hz Temperature = 25 °C				1.				
1	Tan δ : 2.5 % Max.			2.				
2	Initial IR : 10,000 MΩ Min.			3.				
3	Dielectric Strength Test : DC 9,450 V			4.				
4	Case Insulation Test : DC 6,300 V			5.				
5	Temperature Characteristics : Δ C/C = ±10% at -25°C ~ +85°C			6.				
6	Lead Pull Test : 1.0 Kg 5 Seconds.			7.				
7	Coating : Epoxy resin coated			8.				
				9.				
				10.				
APPROVED BY CUSTOMER				REMARK :				
Your Confirmation : ☐ Approval ☐ Conditional Approval ☐ Rejection (Please send a copy for our ref.)				Spec. Applied by EIA RS198 Test Instruments: (1). Capacitance: (a).CHEN HWA 1062 L.C.R.METER (1Khz). (b).ESI410 OR HP 4277 L.C.R.METER(1Mhz). (2). Dissipation Factor: as the Item (1). (3). Insulation Resistance: GENERAL RADIO 1864 MEGOHM METER. (4).Dielectric Strength: PHIHON PUNCTURE TESTER				
Inspected by		Checked by		吳美華		Approved by		許介洲