

**SPECIFICATION FOR APPROVAL**

<b>CERAMIC DISC CAPACITORS</b>								
<b>CUSTOMER:</b>								
Capacitance: <b>330 pF</b>	Tolerance: <b>±10 %</b>	Issue No.						
Temp. Coef. <b>Y5P</b>	Q'ty of Sample: pcs	Issue Day. <b>19/08/2020</b>						
Cust. P/N:	Part No. <b>KB4C331K-L018BD12</b>	W V	<b>15,000</b>	VDC				
Diagram of Dimensions : (Unit : mm)								
			<p>D: <u>12.0 max.</u> T: <u>11.0 max.</u> F: <u>9.5 ±1.5</u> L: <u>25.0 min.</u> d: <u>0.8 ±0.1</u> P: <u>4.0 max.</u></p>					
<b>SPECIFICATION</b>				<b>Initial Test</b>				
				No.	pF	Tanδ	I.R.	T.V.
Frequency = <b>1K Hz</b> Temperature = <b>25 °C</b>				1.				
1	Tan δ : <b>2.5 % Max.</b>			2.				
2	Initial IR : <b>10,000 MΩ Min.</b>			3.				
3	Dielectric Strength Test : DC <b>22,500 V</b>			4.				
4	Case Insulation Test : DC <b>15,000 V</b>			5.				
5	Temperature Characteristics : ΔC/C = <b>±10% at -25°C ~ +85°C</b>			6.				
6	Lead Pull Test : <b>1.0 Kg</b> 5 Seconds.			7.				
7	Coating : Epoxy resin coated			8.				
				9.				
				10.				
<b>APPROVED BY CUSTOMER</b>				<b>Remark :</b>				
Your Confirmation : <input type="checkbox"/> Approval <input type="checkbox"/> Conditional Approval <input type="checkbox"/> Rejection (Please send a copy for our ref.)				Spec. Applied by EIA RS198 Test Instruments: (1). Capacitance: (a).CHEN HWA 1062 L.C.R.METER (1Khz). (b).ESI410 OR HP 4277 L.C.R.METER(1Mhz). (2). Dissipation Factor: as the Item (1). (3). Insulation Resistance: GENERAL RADIO 1864 MEGOHM METER. (4).Dielectric Strength: PHIHON PUNCTURE TESTER				
Inspected by		Checked by	吳美華	Approved by	許介洲			