

SPECIFICATION FOR APPROVAL

CERAMIC DISC CAPACITORS								
CUSTOMER:								
Capacitance: 470 pF	Tolerance: ±10 %		Issue No.					
Temp. Coef. Y5P	Q'ty of Sample: pcs		Issue Day. 18/02/2020					
Cust. P/N:	Part No. KB4C471K-L018BD12		W V 15,000 VDC					
Diagram of Dimensions : (Unit : mm)								
			<p>D: <u>12.0 max.</u> T: <u>8.0 max.</u> F: <u>10.0 ±2.0</u> L: <u>25.0 min.</u> d: <u>0.8 ±0.10</u> P: <u>5.0 max.</u></p>					
SPECIFICATION				Initial Test				
				No.	pF	Tanδ	I.R.	T.V.
Frequency = 1K Hz Temperature = 25 °C				1.				
1	Tan δ : 2.5 % Max.			2.				
2	Initial IR : 10,000 MΩ Min.			3.				
3	Dielectric Strength Test : DC 22,500 V			4.				
4	Case Insulation Test : DC 15,000 V			5.				
5	Temperature Characteristics : ΔC/C = ±10% at -25°C ~ +85°C			6.				
6	Operating Temperature Range : -25°C ~ +100°C			7.				
7	Lead Pull Test : 1.0 Kg 5 Seconds.			8.				
8	Coating : Epoxy resin coated			9.				
				10.				
APPROVED BY CUSTOMER				Remark :				
Your Confirmation : <input type="checkbox"/> Approval <input type="checkbox"/> Conditional Approval <input type="checkbox"/> Rejection (Please send a copy for our ref.)				Spec. Applied by EIA RS198 Test Instruments: (1). Capacitance: (a).CHEN HWA 1062 L.C.R.METER (1Khz). (b).ESI410 OR HP 4277 L.C.R.METER(1Mhz). (2). Dissipation Factor: as the Item (1). (3). Insulation Resistance: GENERAL RADIO 1864 MEGOHM METER. (4).Dielectric Strength: PHIHON PUNCTURE TESTER				
Inspected by		Checked by	吳美華	Approved by	許介洲			