



CONNECTOR	DIM. A ±.03
SMA MALE	1.41
SMA FEMALE	1.30
BNC MALE	1.59
BNC FEMALE	1.65
TNC MALE	1.59
TNC FEMALE	1.65
N MALE	1.32
N FEMALE	1.40
7/16 MALE	2.32
7/16 FEMALE	2.24
4.1/9.5 MALE	1.28
4.1/9.5 FEMALE	1.40
4.3/10 MALE	1.28
4.3/10 FEMALE	1.47

*NOTE: INSERT ATTENUATION VALUE i.e. 006 = 6dB

REV	ECN	DATE	BY	APPR		
-	ISSUED	3-17-82	PT	FDW		
A	3302	6-4-91	TEZ	FDW		
B	3485	12-3-91	PT	FDW		
C	5792	9-11-98	CDJ	FDW		
D	26009	12-15-15	JZ	TEZ		
E	24444	9-26-19	GM	TEZ		
					MATERIAL	PROPRIETARY INFORMATION
					FINISH	ALL SURFACES ARE TO BE FREE OF BURRS, PITS & SCRATCHES
					MODEL	TOLERANCES
					50FH-XXX-5	.XX±.010 .XXX±.005 XX°±.5°
					DESCRIPTION	DWG #
					5 WATT FIXED ATTENUATOR	092-137



JFW INDUSTRIES, INC.

www.jfwindustries.com

PH: 317-887-1340

SCALE FULL

