

SPECIFICATION SHEET

JFW MODEL 50FHAO-XXX-200

FIXED ATTENUATOR

JFW Industries, Inc.
Phone: 317-887-1340
sales@jfwindustries.com
www.jfwindustries.com

Frequency Range DC-3000 MHz

Impedance 50 Ohms nominal

Attenuation Values 1 thru 50 dB in any 1 dB increment

VSWR 1.4:1 maximum
< 1.25:1 typical

Attenuation Accuracy ± 0.5 dB (1-30 dB)
± 0.75 dB (31-50 dB)

RF Input Power (bi-directional) 200 Watts average @ +25°C
Derate to 100 Watts @ +85°C

Peak Power 1000 Watts (1 microsecond pulse)

RF Connector SMA, TNC, BNC, N, 4.1-9.5, 4.3-10.0 or 7/16

Operating Temperature Range -55°C to +100°C

Optional mounting bracket Bracket part number: 004-198
Drawing w/ bracket: 092-5819

Physical Size See outline drawing 092-3728

ECR/ECN #	DATE	REV	APPR / DATE	ECR/ECN #	DATE	REV	APPR / DATE
20288	07/01/2011	H	TRS 07/01/2011	27003	08/29/2016	K	CLK 08/29/2016
20523	08/31/2011	I	TRS 08/31/2011	32758	08/10/2023	L	TRS 08/10/2023
26007	12/14/2015	J	CLK 12/14/2015	32782	08/18/2023	M	TRS 08/18/2023