



CONNECTOR	DIM. A ±.03
SMA MALE	.56
SMA FEMALE	.52
BNC MALE	.80
BNC FEMALE	.60
TNC MALE	.80
TNC FEMALE	.60
N MALE	.96
N FEMALE	.73
7/16 MALE	1.31
7/16 FEMALE	1.22
4.1/9.5 MALE	.96
4.1/9.5 FEMALE	.96
4.3/10 MALE	1.06
4.3/10 FEMALE	1.02

* INSERT NOMINAL dB VALUE i.e. 030 =30dB

REV	ECN	DATE	BY	APPR
-	ISSUED	8-2-01	BZ	TEZ
A	7175	7-10-02	BZ	TEZ
B	7472	4-18-03	TEZ	TEZ
C	7900	6-23-04	RLT	TEZ
D	16122	7-21-18	BZ	TEZ
E	21671	6-21-12	BZ	TEZ
F	26009	12-14-15	JZ	TEZ
G	24444	9-11-19	GM	TEZ



JFW INDUSTRIES, INC.

www.jfwindustries.com

PH: 317-887-1340

MATERIAL	HEATSINK: ALUM ALLOY / CONN: BRASS	PROPRIETARY INFORMATION
FINISH	HEATSINK: BLACK ANODIZE / CONN: NICKEL	ALL SURFACES ARE TO BE FREE OF BURRS, PITS & SCRATCHES
MODEL	50XXX-XXX-25	TOLERANCES .XX±.010 .XXX±.005 XX°±.5°
DESCRIPTION	25 WATT FIXED ATTENUATOR	DWG # 092-3736