

SPECIFICATION SHEET

JFW MODEL 50HF-XXX-100/6

FIXED ATTENUATOR UNI-DIRECTIONAL

JFW Industries, Inc.
Phone: 317-887-1340
sales@jfwindustries.com
www.jfwindustries.com

Frequency Range DC-6 GHz

Impedance 50 Ohms nominal

Attenuation Values 3, 6, 10, 15, 20, 30 and 40 dB

VSWR
1.25:1 maximum DC-1500 MHz
1.35:1 maximum 1500-2500 MHz
1.45:1 maximum 2500-6000 MHz

Attenuation Accuracy	DC-1.5GHz	1.5-2.5GHz	2.5-6GHz
3, 6 dB	±0.50 dB	±0.50 dB	±0.75 dB
10, 15 dB	±0.75 dB	±0.75 dB	±2.50 dB
20, 30 dB	±0.75 dB	±1.00 dB	±1.50 dB
40 dB	±1.50 dB	±1.50 dB	±2.50 dB

RF Input Power
100 Watts average - Input side
Derate linearly to 20 Watts @ +125°C

20 Watts average - Output side

Mounting Directions Mount heat sink fins vertically. Provide space for free air convection flow to occur.

Peak Power 1000 Watts
(5 microsecond pulse, 0.05% duty cycle)

3rd Order Intercept Point -105 dBc typical
(Two 20W tones at 1930 & 1950 MHz - Input only)

RF Connector SMA, N, TNC, 4.3/10.0, or 7/16

Operating Temperature Range -55°C to +125°C

Physical Size Outline drawing: 092-7189 (N M / N F)
092-7189-01 (N F / N M)
092-7219 (N F / N F)
092-7388 (SMA M / SMA F)
092-7389 (SMA F / SMA F)
092-8028 (7/16 M / 7/16 F)
092-8029 (7/16 M / N F)
092-9148 (4.3/10.0 M/F)
092-9460 (TNC)

ECR/ECN #	DATE	REV	APPR / DATE	ECR/ECN #	DATE	REV	APPR / DATE
24328	07/18/2014	D	CLK 07/18/2014	29492	04/30/2019	G	BAC 04/30/2019
28849	07/03/2018	E	CLK 07/03/2018	30084	01/02/2020	H	CLK 01/02/2020
28947	08/13/2018	F	CLK 08/13/2018	30398	05/27/2020	I	CLK 05/27/2020