

SPECIFICATION SHEET

JFW MODEL 50PA-717

LC HANDOVER TEST SYSTEM

JFW Industries, Inc.
Phone: 317-887-1340
sales@jfwindustries.com
www.jfwindustries.com

Frequency Range	2-6 GHz
Configuration	16 X 2 LC Handover Test System (See block diagram 092-7339)
Enclosure Type	19 inch rack mount @ 3RU high
Impedance	50 Ohms nominal
Attenuation Range	0-95 dB in 1 dB steps
Startup/Default States (configurable)	Maximum attenuation (see ATTEN STARTUP command) DHCP enabled (see NET command) 4 Ethernet users (see NET USERS command) Prompts off (see PROMPT command)
VSWR	1.6:1 maximum
Attenuation Accuracy (guaranteed monotonic)	± 0.50 dB 1-3 dB ± 0.75 dB 4-7 dB ± 1.00 dB 8-11 dB ± 1.25 dB or 4% 12-95 dB (whichever is greater)
Insertion Loss	31 dB maximum 25 dB typical @ 2 GHz 29 dB typical @ 6 GHz
Isolation	28 dB minimum (In 1-16 to In 1-16) 18 dB minimum (Out 1 to Out 2)
RF Input Power	+27 dBm average +33 dBm (no damage)
Switching Speed	4 microseconds typical (after command is received and processed) (3 milliseconds typical processing time)
AC Supply	100-240 VAC @ 47-63 Hz 2 Amp 5x20mm "Slo-Blo" AC fuse Littelfuse#215-002, JFW#025-021
Manual Control	20-Button Keypad and LCD display (IP Address configurable via keypad) (Net mask configurable via keypad) (Gateway configurable via keypad) (Baud rate configurable via keypad)

--CONTINUED--

SPECIFICATION SHEET

JFW MODEL 50PA-717

LC HANDOVER TEST SYSTEM

JFW Industries, Inc.
Phone: 317-887-1340
sales@jfwindustries.com
www.jfwindustries.com

Remote Control Ethernet (DHCP, TCP/IP, 10/100, up to 12 users)
RS-232 (up to 115200 Baud)


Remote Commands Attenuator Control Commands:
Atten, Set Attenuator, Read Attenuator, Set
All Attenuators, Read All Attenuators, Read
All Extended, Fade Attenuator, Variable
Attenuator Handover, Block, Set Block, Read
Block, Read All Blocks, Fade Block, Variable
Block Handover

System Commands:
Help, Identification, Store, Recall, Pause,
Net, Serial, Close, Disconnect, MOTD, Date,
Message, Restrict, IDENT, Name, Show Users,
Reboot, Uptime, Prompt

RF Connector N or SMA female

Operating Temperature Range 0°C to +50°C

Physical Size See outline drawing 092-7338



ECR/ECN #	DATE	REV	APPR / DATE	ECR/ECN #	DATE	REV	APPR / DATE
	04/26/2012		CLK 04/26/2012				
28159	10/06/2017	A	CLK 10/06/2017				