


MODEL #	ATTENUATION RANGE
50R-019	0-10dB x 1's
50R-107	0-20dB CONT. VARIABLE
50R-130	0-20dB x 2's
50R-199	0-2dB x .2's
50R-218	0-15dB CONT. VARIABLE
50R-287	0-11dB x 1's

				<b>JFW INDUSTRIES, INC.</b> INDIANAPOLIS, IN		PROPRIETARY INFORMATION	
REV	ECN	DATE	BY	DRAWN BY	CDJ	DATE	12-11-00
A	1349	3-29-86	SM	APPD BY		SCALE	FULL
B	1938	2-25-88	PT	MATERIAL	ALUMINUM ALLOY		
C	3502	12-20-91	TEZ	FINISH	CHEMFILM TCP		
D	3617	5-01-92	PT	DESCRIPTION	50R-XXX: ROTARY ATTENUATOR		
E	4051	9-16-93	TEZ				
F	6085	8-13-99	TEZ				
G	6532	12-11-00	CDJ				
H	6750	6-11-01	CDJ				
J	6695	1-30-02	CMB				
K	12635	4-20-06	ETW				
							ALL SURFACES ARE TO BE FREE OF BURRS, PITS, & SCRATCHES
							TOLERANCES
							FRACTIONAL DIM. ± 1/64
							2 PLACE DECIMAL ± .010
							3 PLACE DECIMAL ± .005
							ANGULAR DIM. ± 1/2 °
							DWG NO. 092-039