


MODEL #	ATTENUATION RANGE
50R-019	0-10dB x 1's
50R-107	0-20dB CONT. VARIABLE
50R-130	0-20dB x 2's
50R-199	0-2dB x .2's
50R-218	0-15dB CONT. VARIABLE
50R-287	0-11dB x 1's

				JFW INDUSTRIES, INC. INDIANAPOLIS, IN		PROPRIETARY INFORMATION	
				DATE: 12-11-00		ALL SURFACES ARE TO BE FREE OF BURRS, PITS, & SCRATCHES	
REV	ECN	DATE	BY	DRAWN BY: CDJ	SCALE: FULL	TOLERANCES	
A	1349	3-29-86	SM	APPROD BY:		FRACTIONAL DIM. ± 1/64	
B	1938	2-25-88	PT	MATERIAL: ALUMINUM ALLOY		2 PLACE DECIMAL ± .010	
C	3502	12-20-91	TEZ	FINISH: CHEMFILM TCP		3 PLACE DECIMAL ± .005	
D	3617	5-01-92	PT	DESCRIPTION: 50R-XXX: ROTARY ATTENUATOR		ANGULAR DIM. ± 1/2 °	
E	4051	9-16-93	TEZ			DWG NO. 092-039	
F	6085	8-13-99	TEZ				
G	6532	12-11-00	CDJ				
H	6750	6-11-01	CDJ				
J	6695	1-30-02	CMB				
K	12635	4-20-06	ETW				