

SPECIFICATION SHEET

JFW MODEL 50SA-559

SWITCH ASSEMBLY

JFW Industries, Inc.
Phone: 317-887-1340
sales@jfwindustries.com
www.jfwindustries.com

Frequency Range	DC-18 GHz
Configuration	2 individually controlled 1P4T normally open self-terminating electro-mechanical RF switches
Enclosure Type	19 inch rack mount @ 2RU high
Startup/Default States (configurable)	RF switches off at startup (see SWITCH command) DHCP enabled (see NET command) 4 Ethernet users (see NET command) Prompts off (see PROMPT command) All of these default settings can be changed by user. Unit can be configured for up to 12 Ethernet users.
Impedance	50 Ohms nominal
VSWR	1.2:1 maximum DC-4 GHz 1.3:1 maximum 4-8 GHz 1.4:1 maximum 8-12.4 GHz 1.5:1 maximum 12.4-18 GHz
Insertion Loss	0.2 dB maximum DC-4 GHz 0.3 dB maximum 4-8 GHz 0.4 dB maximum 8-12.4 GHz 0.5 dB maximum 12.4-18 GHz
Isolation	80 dB minimum DC-4 GHz 70 dB minimum 4-8 GHz 65 dB minimum 8-12.4 GHz 60 dB minimum 12.4-18 GHz
RF Input Power (cold switched)	500 Watts average DC-100 MHz 400 Watts average 100-200 MHz 300 Watts average 200-500 MHz 200 Watts average 500-1000 MHz 100 Watts average 1-4 GHz 90 Watts average 4-8 GHz 70 Watts average 8-12 GHz 60 Watts average 12-18 GHz *2 Watts average for self terminations
Switching Speed	15 milliseconds (after command is received and processed) (3 milliseconds typical processing time)
Manual Control	20-Button Keypad and LCD display (IP Address configurable via keypad) (Net mask configurable via keypad) (Gateway configurable via keypad) (Baud rate configurable via keypad)
Remote Control	Ethernet (DHCP, TCP/IP, 10/100, up to 12 users) RS-232 (up to 115200 Baud)

--CONTINUED--

SPECIFICATION SHEET

JFW MODEL 50SA-559

SWITCH ASSEMBLY

JFW Industries, Inc.
Phone: 317-887-1340
sales@jfwindustries.com
www.jfwindustries.com

Remote Commands

RF Switch Control Commands:
Switch, Set Switch, Read Switch, Set All Switches,
Read All Switches

System Commands:
Help, Identification, Store, Recall, Pause, Net,
Serial, Close, Disconnect, MOTD, Date, Message,
Restrict, IDENT, Name, Show Users, Reboot, Uptime,
Prompt

AC Supply

100-240 VAC @ 47-63 Hz

RF Connector

SMA female

Operating Temperature Range

0°C to +50°C

Physical Size

See outline drawing 092-8673



ECR/ECN #	DATE	REV	APPR / DATE	ECR/ECN #	DATE	REV	APPR / DATE
	07/29/2016		TRS 07/29/2016				