

SPECIFICATION SHEET

JFW MODEL 75FFB-XXX

DC PASSING FIXED ATTENUATOR

JFW Industries, Inc.
Phone: 317-887-1340
sales@jfwindustries.com
www.jfwindustries.com

Frequency Range 950-2150 MHz

Description DC Passing Fixed Attenuator

Impedance 75 Ohms nominal

Attenuation Values 3 to 20 dB in any 1 dB step

VSWR 1.5:1 maximum

Attenuation Accuracy ± 0.5 dB

RF Input Power 1 Watt average

Peak Power 100 Watts

DC Current Handling 2 Amps

DC Breakdown Voltage 50 Volts

DC Resistance 0.1 Ohms

RF Connector BNC or F

Operating Temperature Range -40°C to +85°C

Outline Drawing Numbers 092-3134 (Connector Chart)
092-4120 (BNC F/F)
092-4851 (BNC M/F)
092-2757 (F M/F)

ECR/ECN #	DATE	REV	APPR / DATE	ECR/ECN #	DATE	REV	APPR / DATE
11450	07/06/2005	E	SL 07/06/2005	26700	06/08/2016	H	CLK 06/08/2016
11493	07/15/2005	F	SL 07/15/2005	27494	01/23/2017	I	TRS 01/23/2017
15740	04/23/2008	G	SMR 04/23/2008	28507	02/15/2018	J	TRS 02/15/2018