

SPECIFICATION SHEET
JFW MODEL 75FP-XXX-3G
FIXED ATTENUATOR

JFW Industries, Inc.
 Phone: 317-887-1340
 sales@jfwindustries.com
 www.jfwindustries.com

Frequency Range	DC-3000 MHz
Impedance	75 Ohms nominal
Attenuation Values	1 thru 30 dB in any 1 dB increment
VSWR	1.15:1 maximum DC-1 GHz 1.35:1 maximum 1-3 GHz
Attenuation Accuracy	1 thru 20 dB: ± 0.3 dB DC-1300 MHz ± 0.5 dB 1300-3000 MHz 21 thru 30 dB: ± 0.6 dB DC-1300 MHz ± 1.0 dB 1300-3000 MHz
RF Input Power	0.5 Watts average @ +25°C
Peak Power	100 Watts
RF Connector	N, BNC or F
Operating Temperature Range	-55°C to +125°C
Outline Drawing Numbers	092-2189 (N male/female) 092-2757 (F male/female) 092-4851 (BNC male/female) 092-3134 (Connector Chart)

ECR/ECN #	DATE	REV	APPR / DATE	ECR/ECN #	DATE	REV	APPR / DATE
17625	08/28/2009	E	SMR 08/28/2009	26842	07/20/2016	H	CLK 07/20/2016
22341	01/10/2013	F	CLK 01/10/2013	27494	01/23/2017	I	TRS 01/23/2017
26700	06/08/2016	G	CLK 06/08/2016	28744	05/11/2018	J	CLK 05/11/2018