

SPECIFICATION SHEET
JFW MODEL 50DR-061
DUAL ROTARY ATTENUATOR

JFW Industries, Inc.
 Phone: 317-887-1340
 sales@jfwindustries.com
 www.jfwindustries.com

Frequency Range	DC-2200 MHz
Impedance	50 Ohms nominal
Attenuation Range	0-80 dB in 1 dB steps
VSWR	1.25:1 maximum DC-1000 MHz 1.5:1 maximum 1000-2200 MHz
Insertion Loss	0.6 dB DC-1000 MHz 1.0 dB 1000-2200 MHz
Attenuation Accuracy	± 0.5 dB or 3%
RF Input Power	2 Watts average 1000 Watts peak
Direction of Rotation	Attenuation increases in a Clockwise direction
Indexing	30 degrees with stops at Minimum and maximum
RF Connector	BNC, SMA or N female
Operating Temperature Range	-20°C to +85°C
Physical Size	See outline drawing 092-440 (SMA) 092-051 (BNC or N)

ECR/ECN #	DATE	REV	APPR / DATE	ECR/ECN #	DATE	REV	APPR / DATE
	04/12/1994			9999	05/12/2003	C	TRS 03/05/2004
649	12/11/1996	A		13601	11/14/2006	D	CLK 11/14/2006
672	02/19/1997	B					