

**SPECIFICATION SHEET**

**JFW MODEL 50PM-009**

**PANEL MOUNTED ROTOR**

JFW Industries, Inc.  
Phone: 317-887-1340  
sales@jfwindustries.com  
www.jfwindustries.com

Frequency Range	DC-2200 MHz
Configuration	8 panel mounted rotary attenuators (specifications are for each individual rotor)
Impedance	50 Ohms nominal
Attenuation Range	0-80 dB in 1 dB steps
VSWR	1.25:1 maximum DC-1000 MHz 1.5:1 maximum 1000-2200 MHz
Attenuation Accuracy	± 0.5 dB or 3%
Insertion Loss	0.6 dB DC-1000 MHz 1.0 dB 1000-2200 MHz
RF Input Power	2 Watts average
Indexing	30° on all units with stops at minimum and maximum
RF Connector	BNC, N or SMA female
Operating Temperature Range	-20°C to +85°C
Physical Size	See outline drawing 092-2527

ECR/ECN #	DATE	REV	APPR / DATE	ECR/ECN #	DATE	REV	APPR / DATE
	01/27/1997			11789	08/30/2005	C	BAC 08/30/2005
9999	08/14/2003	A					
4450	02/02/2004	B	CLV 02/02/2004				