

SPECIFICATION SHEET**JFW MODEL 50S-1310****1P8T SELF TERMINATING SOLID STATE RF SWITCH**

JFW Industries, Inc.
Phone: 317-887-1340
sales@jfwindustries.com
www.jfwindustries.com

Frequency Range	20-4300 MHz
Configuration	1P8T Self Terminating
Impedance	50 Ohms nominal
VSWR	1.5:1 maximum
Insertion Loss	2.5 dB maximum 20-1000MHz 3.0 dB maximum 1000-2000MHz 3.5 dB maximum 2000-3000MHz 4.5 dB maximum 3000-4300MHz
Isolation	70 dB minimum to 2000MHz 50 dB minimum to 4300MHz
Switching Speed	10 microseconds
RF Input Power	+20 dBm (20-100MHz) +30 dBm (100-4300MHz)
Control Logic (4 Lines)	See Outline Drawing 092-3658
DC Supply	+24Vdc @ 200 mA maximum +5Vdc @ 150 mA maximum
DC Connector	3M # 3793-5305
RF Connector	SMA female
Operating Temperature Range	0 to +70° C
Physical Size	See outline drawing 092-3658

ECR/ECN #	DATE	REV	APPR / DATE	ECR/ECN #	DATE	REV	APPR / DATE
	03/20/2003		BAC 03/20/2003				
4311	07/21/2003	A	CLV 07/21/2003				
11420	06/28/2005	B	BAC 06/28/2005				