

SPECIFICATION SHEET**JFW MODEL 50S-1422****1P2T SOLID STATE RF SWITCH**

JFW Industries, Inc.
Phone: 317-887-1340
sales@jfwindustries.com
www.jfwindustries.com

Frequency Range	100-500 MHz
Configuration	1P2T
Impedance	50 Ohms nominal
VSWR	1.25:1 maximum
Insertion Loss	0.5 dB maximum
Isolation	55 dB minimum
Switching Speed	40 microseconds (50% TTL to 10% or 90% RF)
RF Input Power	250 Watts average (cold switch) 500 Watts peak (1usec pulse) 100 Watts average (hot switch*)
Control (1 line)	TTL Low for J1-COM TTL High for J2-COM (off port is reflective)
DC Supply	+15 Vdc @ 250 mA +5 Vdc @ 40 mA
RF Connector	BNC, SMA, TNC or N female
Operating Temperature Range	-20°C to +70°C
Storage Temperature Range	-55°C to +85°C
Physical Size	See outline drawing 092-3022

* If switch rate exceeds 1000 cycles per second, external heatsinking will be required to maintain a maximum case temperature of +70°C.

ECR/ECN #	DATE	REV	APPR / DATE	ECR/ECN #	DATE	REV	APPR / DATE
	04/06/2005		BAC 04/06/2005				