



LEANGEN-2450M-6000-E

6kW Solid-State Microwave Generator

LEANGEN-2450M-6000-E is a highly compact microwave generator designed for operation in industrial processing, born to offer all the advantages of solid-state technology to industry professionals aiming at an unprecedented combination of performance and reliability. The generator is fully based on steady **Gallium Nitride (GaN) solid-state technology**, assuring unaltered performance and minimum maintenance burden throughout its extensive life cycle.

LEANGEN-2450M-6000-E is powered by 400Vac 3-phase mains and it features a 0-6kW CW output over WR340 waveguide with exceptional spectral purity at all power levels, operating at 2450MHz. The product comes equipped with a standard industrial bus control interface, allowing easy integration in existing production plants, and water-cooled for long-term reliability in highly intensive workloads.

The generator features accurate real-time measurement of RF operating parameters and automatic safety functions that minimize hardware failures in case of unexpected anomalous operating conditions. Its high parametric flexibility paves the way for future process optimizations and easy operational planning by means of straightforward software upgrade. Being based on solid-state technology, the generator does not require periodical parts replacement, avoiding downtime issues and high operating costs. Moreover, high production repeatability allows future plant extension or potential parts replacement with plug-and-play installation and no need for in-field re-tuning.

The digital heart of **LEANGEN-2450M-6000-E** also allows easy remote monitoring by plant managers and remote support by the manufacturer, simplifying and economising testing and commissioning activities.

QUICK OVERVIEW

Highly compact and top-reliable

400Vac 3P+N power supply

Integrated Synthesizer

6kW CW output power

Robust and efficient GaN technology

Digital fine tuning of all operating parameters

Industrial bus control

Integrated graphic user interface

2450MHz operating frequency

WR340 Output

High efficiency

Water cooled

Modular solid-state design

No downtime issues

No performance degradation over time



LEANGEN-2450M-6000-E

6kW Solid-State Microwave Generator

Technical Specifications

CW Output Power	0-6kW step 10W
Power Modes	Tested with CW and Pulsed modes
Output Connector	WR340
Technology	Fully 50V GaN Solid-State
Output RF Isolation	External output isolator required
Operating Frequency	2450MHz
Power Supply	400Vac 3P+N, 50-60Hz
Power Efficiency	>55%
Forward and Reflected Power Meas.	Real-time
RF IN Connector	N female (available for use with external oscillators)
Control&Monitoring	Standard industrial bus control interface
User Interface	Integrated touch-panel GUI
Cooling	Water cooling
Cooling Water Temperature	18°C – 28°C
Cooling water Flow	≥ 30 liters/min
Size	71x45x33cm (to be confirmed)
Weight	Approx. 60kg (to be confirmed)

