


ALL DESIGN, OPERATIVE AND PROCESS DATA PERTAINING TO THE ARTICLE SHOWN ON THIS SHEET IS THE PROPERTY OF POLYPHASE CORPORATION. THE INFORMATION IS NOT TO BE COPIED, REPRODUCED, REVEALED TO OR APPROPRIATED BY OTHERS WITHOUT THE EXPRESS WRITTEN CONSENT OF POLYPHASE CORPORATION.


REVISIONS

REV	LTR	DATE	ENG	MKTG	Q.A.
D		07/14/04 RS	KCB	SD	LJ
E		12/07/04 RS	KCB	SD	LJ



MAXIMUM CHARACTERISTICS

APPLICATION:
WEATHERIZED, FLANGE OR BULKHEAD MOUNT
FREQUENCY RANGE:
400MHz TO 1200MHz
VSWR:
≤1.1:1 OVER FREQUENCY RANGE
INSERTION LOSS:
≤0.1dB OVER FREQUENCY RANGE
POWER:
300W RMS AVERAGE
TURN ON:
+20Vdc
TURN ON TIME:
4ns FOR 2kV/ns
SURGE:
20kA IEC 61000-4-5 8/20μs WAVEFORM
THROUGHPUT ENERGY:
<25μJ FOR 3kA, 8/20μs WAVEFORM
USER VOLTAGE:
+15Vdc MAX
USAGE CURRENT:
≤4.0A CONTINUOUS
VIBRATION:
1G AT 5Hz TO 100Hz
RELATIVE HUMIDITY:
TO 95%
ENVIRONMENTAL:
MEETS IEC 60529 IP67
MEETS BELLCORE #TA-NWT-000487
PROCEDURE 4.11, WIND DRIVEN (120MPH)
RAIN INTRUSION TEST.
TEMPERATURE:
-50°C TO +85°C STORAGE/OPERATING+85°C



CUSTOMER APPROVAL: _____ DATE: _____

ALL DIMENSIONS SHOWN ABOVE ARE FOR REFERENCE ONLY.

DRAFTER I. BENNETT	DATE 04/03/02	P.O. BOX 9000 MINDEN, NV 89423 TEL: 775-782-2511 FAX: 775-782-4476 DWG NO/PART NO/DESCRIPTION CGXJ+15NFM-A CUSTOMER PRINT			
MECH ENGINEER P. SKROTZKI	DATE 04/04/02				
ELEC ENGINEER K. BARTEL	DATE 04/04/02				
MARKETING P. HEEREN	DATE 04/04/02				
QUALITY DEPT R. MATHEUS	DATE 04/04/02	CAGE CODE 61114	FILE NAME -C1	SCALE 1/1	SHEET 1 OF 1