


ALL DESIGN, OPERATIVE AND PROCESS DATA PERTAINING TO THE ARTICLE SHOWN ON THIS SHEET IS THE PROPERTY OF POLYPHASE CORPORATION. THE INFORMATION IS NOT TO BE COPIED, REPRODUCED, REVEALED TO OR APPROPRIATED BY OTHERS WITHOUT THE EXPRESS WRITTEN CONSENT OF POLYPHASE CORPORATION.


# REVISIONS

REV LTR	DATE	ENG	MKTG	Q.A.
D	12/07/04	KCB	SD	LJ




## MAXIMUM CHARACTERISTICS

APPLICATION:  
WEATHERIZED, FLANGE OR BULKHEAD MOUNT  
FREQUENCY RANGE:  
400MHz TO 1200MHz  
VSWR:  
≤1.1:1 OVER FREQUENCY RANGE  
INSERTION LOSS:  
≤0.1dB OVER FREQUENCY RANGE  
POWER:  
300W RMS AVERAGE  
TURN ON:  
+40Vdc  
TURN ON TIME:  
4ns FOR 2kV/ns  
SURGE:  
20kA IEC 61000-4-5 8/20μs WAVEFORM  
THROUGHPUT ENERGY:  
<25μJ FOR 3kA, 8/20μs WAVEFORM  
USER VOLTAGE:  
+36Vdc MAX  
USAGE CURRENT:  
≤4.0A CONTINUOUS  
VIBRATION:  
1G AT 5Hz TO 100Hz  
RELATIVE HUMIDITY:  
TO 95%  
ENVIRONMENTAL:  
MEETS IEC 60529 IP67.  
CONNECTOR AND LID  
MEETS BELLCORE #TA-NWT-000487  
PROCEDURE 4.11, WIND DRIVEN (120MPH)  
RAIN INTRUSION TEST.  
TEMPERATURE:  
-50°C TO +85°C STORAGE/OPERATING+85°C



CUSTOMER APPROVAL: \_\_\_\_\_ DATE: \_\_\_\_\_

ALL DIMENSIONS SHOWN ABOVE ARE FOR REFERENCE ONLY.

DRAFTER S. HALL	DATE 06/24/02	 P.O. BOX 9000 MINDEN, NV 89423 TEL: 775-782-2511 FAX: 775-782-4476 DWG NO/PART NO/DESCRIPTION CGXJ+36NFNF-A CUSTOMER PRINT		
MECH ENGINEER R. DUNNING	DATE 07/02/02			
ELEC ENGINEER K. BARTEL	DATE 06/25/02			
MARKETING P. HEEREN	DATE 06/26/02			
QUALITY DEPT R. MATHEUS	DATE 06/25/02			
CAGE CODE 61114	FILE NAME -C1	SCALE 1/1	SHEET 1 OF 1	