


ALL DESIGN, OPERATIVE AND PROCESS DATA PERTAINING TO THE ARTICLE SHOWN ON THIS SHEET IS THE PROPERTY OF POLYPHASE CORPORATION. THE INFORMATION IS NOT TO BE COPIED, REPRODUCED, REVEALED TO OR APPROPRIATED BY OTHERS WITHOUT THE EXPRESS WRITTEN CONSENT OF POLYPHASE CORPORATION.

REVISIONS

REV LTR	DATE	ENG	MKTG	Q.A.
A	07/15/04 RS	KCB	SD	LJ



MAXIMUM CHARACTERISTICS

APPLICATION:
WEATHERIZED, FLANGE OR BULKHEAD MOUNT
FREQUENCY RANGE:
800MHz TO 2500MHz

VSWR:
≤1.1:1 OVER FREQUENCY RANGE
INSERTION LOSS:
≤0.1dB OVER FREQUENCY RANGE

POWER:
300W RMS AVERAGE

TURN ON:
+26Vdc

TURN ON TIME:
4ns FOR 2kV/ns

MAX. SURGE:
20kA IEC 61000-4-5 8/20μs WAVEFORM
THROUGHPUT ENERGY:
≤25μJ FOR 3kA, 8/20μs WAVEFORM

USER VOLTAGE:
+24Vdc MAX

USAGE CURRENT:
≤4.0A CONTINUOUS

RELATIVE HUMIDITY:
TO 95%

ENVIRONMENTAL:

LID AND CONNECTORS
MEET IEC 60529 IP67



MEET BELLCORE #TA-NWT-000487

PROCEDURE 4.11, WIND DRIVEN (120MPH)

RAIN INTRUSION TEST.

TEMPERATURE:

-50°C TO +85°C STORAGE/OPERATING



CUSTOMER APPROVAL: _____

DATE: _____

ALL DIMENSIONS SHOWN ABOVE ARE FOR REFERENCE ONLY.

DRAFTER R. SWART	DATE 01/08/04	 P.O. BOX 9000 MINDEN, NV 89423 TEL: 775-782-2511 FAX: 775-782-4476 DWG NO/PART NO/DESCRIPTION DGXJ+24DMDF-A CUSTOMER PRINT		
MECH ENGINEER R. DUNNING	DATE 01/12/04			
ELEC ENGINEER K. BARTEL	DATE 01/08/04			
MARKETING S. DOTTER	DATE 01/09/04			
QUALITY DEPT L. JACQUES	DATE 01/12/04	CAGE CODE 61114	FILE NAME -C1	SCALE 1/1
		SHEET 1 OF 1		