


ALL DESIGN, OPERATIVE AND PROCESS DATA PERTAINING TO THE ARTICLE SHOWN ON THIS SHEET IS THE PROPERTY OF POLYPHASER CORPORATION. THE INFORMATION IS NOT TO BE COPIED, REPRODUCED, REVEALED TO OR APPROPRIATED BY OTHERS WITHOUT THE EXPRESS WRITTEN CONSENT OF POLYPHASER CORPORATION.

REVISIONS

REV LTR	DATE	ENG	MKTG	Q.A.
---------	------	-----	------	------



**MAXIMUM CHARACTERISTICS**

**APPLICATION:**

BULKHEAD, WEATHERPROOF WHEN INSTALLED

**SURGE:**

30kA IEC 61000-4-5 8/20 $\mu$ s WAVEFORM

**FREQUENCY RANGE:**

800MHz TO 2.3GHz @ 1.1:1VSWR

700MHz TO 2.5GHz @ 1.2:1VSWR

**INSERTION LOSS:**

$\leq 0.1$ dB

**CONTINUOUS POWER:**

500W @ 85°C

750W @ 40°C

1kW @ 20°C

(@900MHz)

**LET THROUGH VOLTAGE:**

$\leq \pm 3$  VOLTS FOR 3kA @ 8/20 $\mu$ s WAVEFORM

**THROUGHPUT ENERGY:**

$\leq 0.5\mu$ J FOR 3kA @ 8/20 $\mu$ s WAVEFORM

**VIBRATION:**

1G @ 5Hz TO 100Hz

**TEMPERATURE:**

-40°C TO +85°C STORAGE/OPERATING

**ENVIRONMENTAL:**

MEETS BELLCORE #TA-NWT-000487


PROCEDURE 4.11, WIND DRIVEN (120MPH)

RAIN INTRUSION TEST.

MEETS IEC 60529 IP65.

CUSTOMER APPROVAL: \_\_\_\_\_ DATE: \_\_\_\_\_

ALL DIMENSIONS SHOWN ABOVE ARE FOR REFERENCE ONLY.

DRAFTER R. SWART	DATE 07/31/03	 P.O. BOX 9000 MINDEN, NV 89423 TEL: 775-782-2511 FAX: 775-782-4476 DWG NO/PART NO/DESCRIPTION <b>DSXL-D</b> <b>CUSTOMER PRINT</b>	
MECH ENGINEER R. DUNNING	DATE 08/13/03		
ELEC ENGINEER J. JONES	DATE 08/13/03		
MARKETING S. DOTTER	DATE 08/13/03		
QUALITY DEPT L. JACQUES	DATE 08/13/03		
CAGE CODE 61114	FILE NAME -C1	SCALE 1/1	SHEET 1 OF 1