




ALL DESIGN, OPERATIVE AND PROCESS DATA PERTAINING TO THE ARTICLE SHOWN ON THIS SHEET IS THE PROPERTY OF POLYPHASER CORPORATION. THE INFORMATION IS NOT TO BE COPIED, REPRODUCED, REVEALED TO OR APPROPRIATED BY OTHERS WITHOUT THE EXPRESS WRITTEN CONSENT OF POLYPHASER CORPORATION.

REVISIONS

REV LTR	DATE	ENG	MKTG	Q.A.
A	09/08/98 JC	TK	--	RM
B	04/03/01 JC	KCB	PH	RM



MAXIMUM CHARACTERISTICS

SURGE:
18kA IEC 1000-4-5 8/20μs WAVEFORM 110 JOULES

TURN-ON:
+3Vdc±10% @ 1mA

FREQUENCY RANGE:
dc TO 200MHz

VSWR:
≤1.1 TO 1 OVER FREQUENCY RANGE

INSERTION LOSS:
<0.3dB OVER FREQUENCY RANGE

TEMPERATURE:
-50°C TO 150°C

CUSTOMER APPROVAL: _____ DATE: _____

ALL DIMENSIONS SHOWN ABOVE ARE FOR REFERENCE ONLY.

DRAFTER K. MUNRO	DATE 06/10/96	PolyPhaser® P.O. BOX 9000, MINDEN, NV 89423-9000 (775) 782-2511 FAX (775) 782-4476 IS-75BB-DS-3 CUSTOMER PRINT			
MECH ENGINEER -----	DATE -----				
ELEC ENGINEER K. BARTEL	DATE 06/10/96				
MARKETING -----	DATE -----				
QUALITY DEPT R. MATHEUS	DATE 06/10/96	CAGE CODE 61114	FILE NAME -C1	SCALE 1/2	SHEET 1 OF 1