




ALL DESIGN, OPERATIVE AND PROCESS DATA PERTAINING TO THE ARTICLE SHOWN ON THIS SHEET IS THE PROPERTY OF POLYPHASER CORPORATION. THE INFORMATION IS NOT TO BE COPIED, REPRODUCED, REVEALED TO OR APPROPRIATED BY OTHERS WITHOUT THE EXPRESS WRITTEN CONSENT OF POLYPHASER CORPORATION.

REVISIONS

REV LTR	DATE	ENG	MKTG	Q.A.
A	02/07/97	KCB	--	RM
B	07/08/03 SH	RD	SD	LJ



MAXIMUM CHARACTERISTICS

SURGE:
18kA IEC 61000-4-5 8/20µs WAVEFORM 110J

TURN-ON:
7Vdc

TURN-ON TIME:
4ns FOR 2kV/ns

FREQUENCY RANGE:
DC TO 30MHz

VSWR:
<1.1:1 OVER FREQUENCY RANGE

INSERTION LOSS:
≤0.3dB OVER FREQUENCY RANGE

USER CURRENT:
3.0Adc CONTINUOUS

TEMPERATURE:
-55°C TO +125°C STORAGE/OPERATING +50°C

CUSTOMER APPROVAL: _____ DATE: _____

ALL DIMENSIONS SHOWN ABOVE ARE FOR REFERENCE ONLY.

DRAFTER J. CALLISTER	DATE 11/01/96	 P.O. BOX 9000 MINDEN, NV 89423 TEL: 775-782-2511 FAX: 775-782-447 DWG NO/PART NO/DESCRIPTION IS-75FB/6 CUSTOMER PRINT			
MECH ENGINEER _ _ _ _	DATE _ _ _				
ELEC ENGINEER T. KULBIEDA	DATE 12/13/96				
MARKETING _ _ _ _	DATE _ _ _				
QUALITY DEPT R. MATHEUS	DATE 12/18/96	CAGE CODE 61114	FILE NAME -C1	SCALE 1/1	SHEET 1 OF 1