




ALL DESIGN, OPERATIVE AND PROCESS DATA PERTAINING TO THE ARTICLE SHOWN ON THIS SHEET IS THE PROPERTY OF POLYPHASER CORPORATION. THE INFORMATION IS NOT TO BE COPIED, REPRODUCED, REVEALED TO OR APPROPRIATED BY OTHERS WITHOUT THE EXPRESS WRITTEN CONSENT OF POLYPHASER CORPORATION.

REVISIONS

REV LTR	DATE	ENG	MKTG	Q.A.
A	08/13/96	TK	--	RM
B	11/14/96	LC	--	RM
C	04/30/98 _{JC}	LC	--	RM
D	02/19/01 _{IB}	LC	TE	RM



MAXIMUM CHARACTERISTICS

SURGE:
 18kA IEC 1000-4-5 8/20μs WAVEFORM 110 JOULES
 TURN ON:
 +30Vdc ±10%
 TURN ON TIME:
 <4ns FOR 2kV/ns
 USER CURRENT:
 2.5Adc CONTINUOUS
 FREQUENCY RANGE:
 400MHz TO 960MHz
 VSWR:
 ≤1.2 TO 1 OVER FREQUENCY RANGE
 INSERTION LOSS
 ≤0.3 dB OVER FREQUENCY RANGE
 TEMPERATURE:
 -40°C TO +85°C STORAGE/OPERATING +50°C

CUSTOMER APPROVAL: _____ DATE: _____

ALL DIMENSIONS SHOWN ABOVE ARE FOR REFERENCE ONLY.

DRAFTER PJ PARSONS	DATE 01/26/96	PolyPhaser® P.O. BOX 9000, MINDEN, NV 89423-9000 (775) 782-2511 FAX (775) 782-4476 DWG NO/PART NO/DESCRIPTION IS-GC50LN+26-MA CUSTOMER PRINT		
MECH ENGINEER - - - - -	DATE - - - - -			
ELEC ENGINEER T. KULBIEDA	DATE 03/12/96			
MARKETING - - - - -	DATE - - - - -			
QUALITY DEPT R. MATHEUS	DATE 03/12/96	CAGE CODE 61114	FILE NAME -C1	SCALE 1/1
		SHEET 1 OF 1		