


ALL DESIGN, OPERATIVE AND PROCESS DATA PERTAINING TO THE ARTICLE SHOWN ON THIS SHEET IS THE PROPERTY OF POLYPHASER CORPORATION. THE INFORMATION IS NOT TO BE COPIED, REPRODUCED, REVEALED TO OR APPROPRIATED BY OTHERS WITHOUT THE EXPRESS WRITTEN CONSENT OF POLYPHASER CORPORATION.

REVISIONS				
REV LTR	DATE	ENG	MKTG	Q.A.
A	07/02/97	KCB	--	RM
B	07/18/01	JJ	PH	LJ



MAXIMUM CHARACTERISTICS
SURGE: 20kA IEC 1000-4-5 8/20μs WAVEFORM 138 JOULES
TURN-ON: 1200Vdc Vt: 1800V
TURN-ON TIME: 7ns FOR 2kV/ns
FREQUENCY RANGE: 890MHz TO 980MHz
VSWR: ≤1.1:1 OVER FREQUENCY RANGE
INSERTION LOSS: ≤0.1dB OVER FREQUENCY RANGE
MAX POWER: 750W SINGLE CHANNEL
TEMPERATURE: -25°C TO +50°C STORAGE/OPERATING

NOTES:
 1 PROTECTIVE CAP OVER CONNECTOR.

CUSTOMER APPROVAL: _____ DATE: _____
 ALL DIMENSIONS SHOWN ABOVE ARE FOR REFERENCE ONLY.

DRAFTER J. CALLISTER	DATE 06/30/97	PolyPhaser® P.O. BOX 9000, MINDEN, NV 89423-9000 (775) 782-2511 FAX (775) 782-4476 DWG NO/PART NO/DESCRIPTION IS-PS50HN-ME CUSTOMER PRINT			
MECH ENGINEER -	DATE -				
ELEC ENGINEER K. BARTEL	DATE 07/10/97				
MARKETING -	DATE -				
QUALITY DEPT R. MATHEUS	DATE 07/14/97	CAGE CODE 61114	FILE NAME -C1	SCALE 1/1.25	SHEET 1 OF 1