




ALL DESIGN, OPERATIVE AND PROCESS DATA PERTAINING TO THE ARTICLE SHOWN ON THIS SHEET IS THE PROPERTY OF POLYPHASER CORPORATION. THE INFORMATION IS NOT TO BE COPIED, REPRODUCED, REVEALED TO OR APPROPRIATED BY OTHERS WITHOUT THE EXPRESS WRITTEN CONSENT OF POLYPHASER CORPORATION.

REVISIONS

REV	LTR	DATE	ENG	MKTG	Q.A.
D		03/15/99 _{JC}	AG	TF	RM
E		01/10/01 _{IB}	KCB	PH	RM



MAXIMUM CHARACTERISTICS

SURGE:
20kA IEC 1000-4-5 8/20μs WAVEFORM

TURN-ON:
+17Vdc, -1Vdc

TURN-ON TIME:
4ns FOR 2kV/ns

USER CURRENT:
2.5Adc CONTINUOUS

FREQUENCY RANGE:
1.2GHz TO 2.0GHz

VSWR:
≤1.1 TO 1 OVER FREQUENCY RANGE

INSERTION LOSS:
≤0.1dB OVER FREQUENCY RANGE

TEMPERATURE:
-50°C TO +125°C STORAGE/OPERATING +60°C

CUSTOMER APPROVAL: _____ DATE: _____

ALL DIMENSIONS SHOWN ABOVE ARE FOR REFERENCE ONLY.

DRAFTER R. DUNNING	DATE 03/28/95	PolyPhaser® P.O. BOX 9000, MINDEN, NV 89423-9000 (775) 782-2511 FAX (775) 782-4476 DWG NO/PART NO/DESCRIPTION MR50LNZ+15 CUSTOMER PRINT			
MECH ENGINEER -----	DATE -----				
ELEC ENGINEER J. JONES	DATE 03/28/95				
MARKETING -----	DATE -----				
QUALITY DEPT R. MATHEUS	DATE 03/28/95	CAGE CODE 61114	FILE NAME -C1	SCALE 1/1	SHEET 1 OF 1