

# WSB™ Weather Seal Strain Relief Boots

For LMR®-195-200, LMR®-240,  
LMR®-400 & LMR®-600

ISO 9001 Certified

- *Combination strain relief and weather seal boot*
- *Eliminates the need for a heat gun to shrink the standard heat shrink sleeve*
- *Fits the most popular LMR®-195-200, 240, 400 & 600 EZ connectors*
- *IP-67 rated*
- *Convenient 10 pack*



The WSB™ weather seal strain relief boots work with the most popular EZ crimp connectors for LMR®-195-200, 240, 400 and 600.

The soft silicone boot weatherproofing kits replace older weatherproofing methods, require no heat and only simple and easy hand assembly for valuable time saving in the field.

The WSB™ weather seal strain relief boots are IP67 rated and both RoHS and REACH Compliant.

Supplied in a convenient 10 pack, the WSB™ kits contain four pouches of silicone lubricant to facilitate installation of the boots.

# WSB™ Weather Seal Strain Relief Boots

Connector Compatibility							
WSB-195-200		WSB-240		WSB-400		WSB-600	
Part #	Description	Part #	Description	Part #	Description	Part #	Description
3190-6140	EZ-195-SM-X	3190-2726	EZ-240-TM-RA-X	3190-2524	EZ-400-716M-X	3190-2642	TC-600-716M-X
3190-6141	EZ-195-BM-X	3190-2868	EZ-240-BM-RA-X	3190-2597	TC-400-716M-X	3190-2546	EZ-600-716M-RA-X
3190-2880	TC-195-NMH-X	3190-2893	EZ-240-NMH-X	3190-2545	EZ-400-716M-RA-X	3190-2816	TC-600-NF-X
3190-2425	TC-195-NMH-RA-D	3190-2894	EZ-240-QM-X	3190-2590	EZ-400-NMH-X	3190-2817	EZ-600-NF-X
3190-2878	TC-195-SM-SS-X	3190-2897	EZ-240-SM-X	3190-2626	TC-400-NMH-X	3190-2627	EZ-600-NMH-X
3190-2879	TC-195-TM-X	3190-6143	EZ-240-NMH-RA-X	3190-2293	TC-400-NMH-RA-D	3190-2628	TC-600-NMH-X
3190-6384	EZ-195-QF-X	3190-6204	EZ-240-TF-X	3190-3049	EZ-400-TF-X	3190-6123	EZ-600-QNM-X
3190-6208	EZ-195-QNM-X	3190-2896	TC-240-SF-BH-SS-X	3190-3051	TC-400-TF-X	3190-6136	TC-600-SCM-X
3190-6166	EZ-195-TF-RP-X	3190-2898	TC-240-SM-SS-X	3190-2533	EZ-400-TM-X	3190-3050	EZ-600-TF-X
3190-6142	EZ-195-TM-RP-X			3190-2532	TC-400-TM-X	3190-3052	TC-600-TF-X
3190-6007	EZ-200-SF-SS-X			3190-2800	EZ-400-TM-RA-X	3190-2531	EZ-600-TM-X
3190-2882	TC-200-NMH-X			3190-2818	EZ-400-NF-X	3190-2530	TC-600-TM-X
3190-2886	EZ-200-NMH-X			3190-2815	TC-400-NF-X		
3190-2883	TC-200-BM-X			3190-2803	EZ-400-NF-PM-X		
3190-6006	EZ-200-SM-RA-SS-X			3190-2805	TC-400-NF-PM-X		
3190-2884	TC-200-TF-X			3190-2852	EZ-400-BM-X		
3190-2885	EZ-200-TM-X			3190-2847	EZ-400-BM-RA-X		
3190-6008	EZ-200-TM-RA-X			3190-2961	EZ-400-NMH-PL-X		
				3190-2962	TC-400-NMH-PL-X		
				3190-2969	EZ-400-4195M-X		
				3190-2968	EZ-400-4195F-X		
				3190-2979	EZ-400-QNM-X		
				3190-2980	EZ-400-QNF-X		
				3190-2981	EZ-400-QNM-RA-X		
				3190-6011	EZ-400-QNF-BH-X		

Mechanical/Environmental Specifications		
	Test Method	Value
Hardness	DIN 53505	Shore A
Density at 20°C	DIN 51757	1.19 g/cm <sup>3</sup>
Elongation at Break	DIN 53504 S1	300%
Rebound Resilience	DIN 53512	50%
Tear Strength	ASTM D624-B	18 N/mm
Compression Set	DIN ISO 815-B	12%
Operating Temperature		-40°C to 85°C

**Construction:**

Material: Silicone rubber

Color: Black

Lubricant: Silicone grease

**Ordering information:**

Part Number - Stock Code

WSB-195-200 3109-445

WSB-240 3109-400

WSB-400 3109-394

WSB-600 3109-401



World Headquarters: 358 Hall Avenue, Wallingford, CT 06492 • Tel: 203-949-8400, 1-800-867-2629 Fax: 203-949-8423

International Sales: +1 203-949-8503 • +1 800-867-2629

China Sales: TMC Building 4, No. 318 Yuanshan Road, Xinzhuang Industrial Park, Shanghai, China 201108 Tel: 86-21-5176-1209 Fax: 86-21-64424098  
www.timesmicrowave.com

© 2017, Times Microwave Systems, Wallingford, CT 06492

WSB-06/17